

CHRONOS 4K12

HIGH-SPEED CAMERA

Slow-motion video serves to captivate audiences, analyze issues, gather new data, and enhance creative visualizations. The Chronos 4K12 high-speed camera revolutionizes slow-motion video capture while maintaining a compact body and a built-in touchscreen.

Its user-friendly design and portability make it an ideal choice for a wide range of use cases, from research and development to professional cinematography and media creation. Delivering 1,397 frames per second in 4K, the Chronos 4K12 establishes itself as the world's fastest 4K camera.

AVAILABLE IN COLOR AND MONOCHROME

MAIN FEATURES

ULTRA HIGH-RESOLUTION

Up to 1,397 FPS @ 4096 x 2160 **4K**

FLEXIBLE WINDOWING

Adjustable up to 29,002 FPS @ 128 x 32

STANDALONE OPERATION

A built-in 5" touchscreen allow for easy recording and review. Additional external battery required for field work (not included).



RESOLUTION & FRAME RATES

CAPTURE RESOLUTION	8-BIT 16.7 Million Colors	10-BIT 1.07 Billion Colors	12-BIT 68.7 Billion Colors
4096 x 2160 4K	1,397 FPS	1,006 FPS	481 FPS
3840 x 2160	1,491 FPS	1,006 FPS	481 FPS
2048 x 2016	2,065 FPS	1,082 FPS	518 FPS
1920 x 1080 HD	3,651 FPS	1,947 FPS	942 FPS
1280 x 1024	3,856 FPS	2,060 FPS	998 FPS
1280 x 720	5,153 FPS	2,793 FPS	1,366 FPS
768 x 576	6,337 FPS	3,479 FPS	1,717 FPS
512 x 480	7,351 FPS	4,082 FPS	2,030 FPS
384 x 256	11,729 FPS	6,847 FPS	3,533 FPS
1280 x 96	20,413 FPS	13,268 FPS	7,495 FPS
128 x 32	29,002 FPS	21,231 FPS	13,590 FPS



Lens not included

RAW OR COMPRESSED

Save files as CinemaDNG (Raw), MPEG-4 (Compressed) and TIFF (Uncompressed) formats.

INTERCHANGEABLE LENS MOUNTS

C, E, EF, F, MFT and PL lens mount plates available. All lens mounts are passive.

REST API for automation. Network connection via USB-C to Ethernet or WiFi adapter.

INDUSTRIES

Academic Research

Media Production

Industrial / Manufacturing

Sports / Biomechanics

Engineering / R&D


Wildlife

CAMERA OVERVIEW

CAMERA	
Model	Color or Monochrome
Imaging	4096 x 2160 @ 1,397 FPS
Memory	128GB
Record Time	11 seconds (128GB) at max resolution
Lens Mount	C, E, F, EF, MFT and PL Mounts (Passive mounts)
Backfocus	Field adjustable via included shim kit
IR Filter	650nm, user removable
Display	5" 800x480 touchscreen, 1000 nit daylight visible
Enclosure	Anodized CNC machined aluminum
Cooling	Active cooling, variable-speed fans
Dimensions	188mm x 111mm x 53mm (7.40" x 4.37" x 2.08") w/o lens
Weight	1.32 kg (2.91 lbs) without lens



CAMERA SPECIFICATIONS - CHRONOS 4K12 HIGH-SPEED CAMERA

INPUTS/OUTPUTS		TRIGGER MODES	
Power Input	12-24V 60W (5.5/2.5mm barrel jack, positive tip)	End Trigger	Records until a defined delay after trigger
Network	Gigabit Ethernet via USB-C Adapter	Toggle	Starts and stops with button press
Trigger	2 trigger inputs / frame strobe outputs (4-pin 3.5mm TRRS Connector) Adjustable input threshold 0 to 6.6V. Included TRRS to BNC splitter cable accessory.	Exposure Trigger	External signal sets synchronization frame-rate
Video Out	HDMI Live Display-All common resolutions including: 4096 x 2160 at 24/25/30/50/60 FPS 3840 x 2160 at 24/25/30/50/60 FPS 1920 x 1080 at 24/25/30/50/60 FPS 1280 x 720 at 24/25/30/50/60 FPS	Shutter Gating	External signal sets the exposure synchronization and frame-rate
USB	USB-C Port 1: 3.2 Gen 1, 5 Gbps (Peripheral) USB-C Port 2: 3.2 Gen 2x2, 20 Gbps (Peripheral, SSDs)	Frame Sync Output	Outputs a signal indicating its frame rate and exposure
VIDEO FORMATS		SOFTWARE	
Compressed	Standardized H.264 AVC, or H.265 HEVC MPEG-4 Video Files	API	HTTP REST Interface, Open-source codebase
RAW	Standard Adobe CinemaDNG raw files	NETWORK CONTROL	
TIFF	Standard TIFF files with timestamps	Network Control	REST API via optional Ethernet or WiFi adapters
Storage Devices	Internal 1 TB NVMe SSD, SD Card, USB-C SSD, or SMB/NFS network drives	RECORDING MODES	
IMAGE SENSOR		Normal	Records into the ring buffer. Once a trigger occurs, video can be reviewed and saved.
Resolution	4096 x 2160 @ 1,397 FPS Maximum 128x32 @ 29,002 FPS Minimum	ASSISTIVE	
Speed	12.4 Gigapixels per second	Focus Aid	Highlights sharp edges to aid focusing
Dimensions	20.74mm x 9.79mm 4/3" format, 10-Megapixel, 2x Crop Factor	Zebras	Rolling diagonal lines indicate clipped (overexposed) areas
Pixel Pitch	4.5um	Histogram	Graphically represent brightness and distribution of light in the image
Sensitivity (ISO)	Color - ISO 100 to 400 Mono - ISO 200 to 800	Overlay	Displays frame and time information on top of footage
Shutter	Electronic global shutter, 1/fps to 1us (1/1,000,000 s)	ENVIRONMENTAL	
		Operating Temperature	0 °C to +40 °C (32 °F to +104 °F)
REGULATORY COMPLIANCE			
USA	FCC - 47 CFR Part 15	REGULATORY COMPLIANCE	
Canada	ISED ICES-Gen Iss.1 & ICES-003 Iss.7	REGULATORY COMPLIANCE	
EU / UK / AUS / NZ	CE EN IEC 61000-6-3-2021, 61000-6-2:2019	REGULATORY COMPLIANCE	
Korea	KS C 9610-6-3:2017, 9610-6-2:2019	REGULATORY COMPLIANCE	
Japan	VCCI-CISPR32:2016	SERVICE & SUPPORT	
<p>Standard 1 year warranty. Optional 1 and 2 year extensions available. Chronos high-speed cameras benefit from free software updates, which offer continuous additions and improvements to in-camera features. Support, tutorials, and software updates are available online at support.krontech.ca</p>			
			